

TECHNICAL INFORMATION SHEET

Reel-Fast Collated Seam Plates

TIS #1110

ITEM NUMBER:

6" W56TPOPL06

12" W56TPOPL12



Description:

Reel-Fast Collated HD Seam Plates are specifically designed to be used for the attachment of Firestone UltraPly™ TPO. The Reel-Fast Collated Seam Plates are to be used in conjunction with Firestone Heavy-Duty or All-Purpose Fasteners into steel, wood or concrete decks. The plates are packaged in a clear plastic film which is rolled onto a plastic reel. The reel has cardboard flanges to assist in unrolling the plates onto the TPO membrane. A plastic tie is looped around the reel and flange assembly to provide a handle to assist in the placement of the plates.

Method of Application:

Each Reel-Fast coil will allow 500 seam plates to be quickly placed in a seam. HD Seam plates shall unroll with Eyehooks™ facing down on the membrane and the “Firestone” facing up. After attaching the first two to three plates, unroll the plates along the seam and fasten as required. To ensure that the plates do not shift, a plate should be fastened to the deck every 5’, or as needed as they are unrolled.

Storage:

- Store in unopened original containers protected from the weather.

Precautions:

- Reel-Fast may only be used with single-weld TPO systems.

Compliance:

Plastic Film

Post Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 0%
 Manufacturing Location: Elk Grove Village, IL

HD Seam Plate

Post Consumer Recycled Content: 0%
 Post Industrial Recycled Content: 21%
 Manufacturing Location: Elk Grove Village, IL

Packaging:

| | |
|----------------|---------------------------|
| <i>Reel:</i> | 500 HD Seam Plates |
| <i>Weight:</i> | 25 lbs (11.3 kg) per reel |
| <i>Carton:</i> | Two reels |
| <i>Pallet:</i> | 20 cartons |

Physical Properties:

Minimum Performance

| | |
|----------------------|---|
| <i>Plastic Film:</i> | Low density Polyethylene Plastic Film |
| <i>Reel:</i> | Spaced at 6” o.c., one reel will cover 250 linear feet of seam. Spaced at 12” o.c., one reel with cover 500 linear feet of seam. |



Eyehook™ is trademark of OMG Inc.

Please Contact your Firestone Technical Coordinator at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.