TECHNICAL INFORMATION SHEET

Firestone BUILDING PRODUCTS

Polymer Fastener Plate

Item Description
Pail: 1,000 Pieces

Item Number
W56RAC4502

Product Information

Description:

The Firestone Polymer Fastener Plate is specifically designed to be used with Firestone Polymer Fastener for attaching Firestone Reinforced Perimeter Fastening (RPF) Strips as specified in Firestone Specifications and Details.

Product Packaging

Pail:	1,000 pieces
Pail Weight:	34 lb (15.42 kg) per pail
Pallet:	40 pails

Method of Application:

Position plates along the Reinforced Perimeter Fastening (RPF) Strip as specified by Firestone Specifications and Details. Attach plates to roof deck using the Firestone Polymer Fastener. Install plates with “Firestone” and “This Side Up” showing.

Storage:

Store in unopened original containers protected from the weather.

Precautions:

1. Do not overdrive or underdrive fastener.
2. Plates are designed to anchor Reinforced Perimeter Fastening (RPF) Strips only**.**
3. Avoid field seams directly over insulation plates where possible.

LEED® Information:

Postconsumer Recycled Content: 0%
Preconsumer Recycled Content: 0%
Manufacturing Location: New Rochelle, NY

FM APPROVED

Physical Properties

Property	Typical Performance
Material:	Galvalume® Sheet Steel
Material Thickness:	0.017" (0.43 mm)
Diameter:	2 1/4" (57 mm)
Corrosion Resistant Coating:	Meets FM No. 4470 Criteria
Pull Through Resistance:	400 lbf (181.4 kgf) from center hole

Galvalume® is a registered trademark of BIEC International, Inc.

Please contact your Firestone Roof Systems Advisor at 1-800-428-4511 for further information.

This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.