

Firestone LVOC Bonding Adhesive for EPDM and TPO



Better for the air. Better for the earth.

Now Firestone brings you an LVOC solvent-based bonding adhesive that's easier to use than water-based alternatives—and just as easy on the environment.

It's part of a family of adhesives from Firestone designed to help minimize harmful effects on the environment and keep your project in compliance with the Ozone Transport Commission's (OTC) member states' policies on volatile organic compounds (VOCs).



Features:

- LVOC solvent-based formulation
- Compatible with both EPDM and TPO membranes
- Bonds membranes to approved insulations in addition to wood, metal, masonry and other acceptable substrates
- Faster dry time than competitive solvent-based products
- Compliant with the OTC regulations on VOCs

Benefits:

- Comparable application to standard solvent-based bonding adhesives
- High performance with good adhesion characteristics
- Year-round application, unlike water-based adhesives
- Offers an environmentally friendly solution at a good value

Firestone
BUILDING PRODUCTS
NOBODY COVERS YOU BETTER™

Firestone Quality

At Firestone Building Products, we're committed to brighter ideas for a greener planet. From our new EnviroReady™ Roofing System Warranty Program to innovative products like our new LVOC adhesives and primers, Firestone is making sure we put our global responsibility into action.



For years, the building industry has been working to reduce VOCs, a class of chemicals that can create air pollution which contributes to health problems. Emissions from VOCs contribute greatly to outdoor smog when they react with other hydrocarbons, nitrogen oxides and sunlight.

With the introduction of new LVOC adhesives and primers, Firestone is doing its part to help ensure safer conditions for installers and friendlier products to the environment.

All Firestone Building Product facilities have their environmental management systems registered to ISO 14001:2004.

Firestone
BUILDING PRODUCTS
NOBODY COVERS YOU BETTER™
www.firestonegreen.com

Firestone Building Products
250 West 96th St., Indianapolis, IN 46260
Corporate Office: 1-800-428-4442 • 317-575-7000 • Fax: 317-575-7100
www.firestonebpco.com

International Offices:
Firestone Building Products Europe
Ikaroslaan 75 - 1930 Zaventem, Brussels, Belgium
+32 2 7114450 • Fax: +32 2 7212718

Firestone Building Products Canada
2835 Argenta Rd., Unit #2
Mississauga, ON L5N 8G6
1-888-292-6265 • 905-363-3150 • Fax: 877-666-3022

Firestone Building Products Latin America
8200 NW 52 Terrace, Suite #107
Miami, FL 33166
305-471-0117 • Fax: 305-471-0377



This green product printed on recycled paper.

Firestone Single-Ply LVOC Bonding Adhesive for EPDM and TPO

PHYSICAL PROPERTIES

Base: Polychloroprene Rubber

Color: Yellow

Solvents: Acetone; Tert-butyl acetate; ethyl acetate

Solids: 22% (min)

Viscosity: 3300-3800 Centipoise, R.V.F. Brookfield, #3 Spindle @ 10RPM

Weight/Gallon: 7.45± 0.15 lb/gal (0.893 kg/L ± 0.018 kg/L)

Specific Gravity: 0.893

Flash Point: 2° F (-19° C)

VOC Content: 218 g/L*

Available in 5-gallon (18.9 liter) pails.

COMPATIBLE DECKS

- Approved insulations
- Wood
- Metal
- Masonry
- Other acceptable substrates

LEED INFORMATION

Post Consumer Recycled Content: 0%
Post Industrial Recycled Content: 0%
Manufacturing Locations: South Bend, IN

CODE APPROVALS

UL and FM code approvals are available at www.firestonebpco.com



*To ensure compliance in your area, please consult your local regulatory agency.