

# TECHNICAL INFORMATION SHEET

## QuickSeam™ SA Patch For Conduit Flashing

TIS #1443

ITEM NUMBER: W56RAC1621

### Description:

RubberGard™ QuickSeam SA Patch for Conduit Flashing ("QS SA Patch for Conduit Flashing") consists of 18" X 18" Standard RubberGard EPDM membrane fully and completely factory laminated to QuickSeam tape with a 3 ¼" diameter hole die-cut in the center. It can be used to flash the flange of QuickSeam Conduit Flashings in conjunction with RubberGard EPDM roofing systems where allowed by Firestone specifications.



QuickSeam tape is used as the tape adhesive to field splice QS SA Patch for Conduit Flashing to primed flanges of QuickSeam Conduit flashings and RubberGard membrane. The polymeric release liner protects the tape until field application, and is perforated to allow removal of the liner in separate sections.

### Method of Application:

1. Prime all surfaces (membrane and flanges) to receive QS SA Patch for Conduit Flashing using QuickPrime™ Plus Primer; Single-Ply QuickPrime; or QuickPrime Plus LVOC Primer scrub applied with QuickScrubber™ Pad and Handle.
2. Allow primer to flash off. Use Touch-Push test to verify primer readiness.
3. Remove release liner in sections to mate QS SA Patch for Conduit flashing to primed substrates only when QS SA Patch for Conduit Flashing is properly positioned over primed substrate.
4. Roll the freshly mated QS SA Patch for Conduit Flashing with silicone coated rubber hand roller to ensure proper mating.
5. Apply seam edge treatment at all lap edges of the QS SA Patch for Conduit Flashing: the perimeter and the die-cut center hole.
6. Refer to Application Instructions included in each cartons for specifics.

### Storage:

- Store in original unopened containers indoors at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Do not store on roof in direct sunlight or at temperatures above 100 °F (37.7 °C).
- When exposed to lower temperatures; restore to room temperature prior to use.
- Shelf life of one year can be expected when stored in original container at temperatures between 60 °F (15.6 °C) and 80 °F (26.7 °C).
- Shelf life will be shortened if exposed to elevated temperatures.

### Compliance:

Post Consumer Recycled Content: 0%  
Pre Consumer Recycled Content: 0%  
Manufacturing Location: Michigan Center, MI

### Packaging:

Pieces	25 Pieces per carton
Pallet	20 cartons per pallet

**NOTE:** QuickScrubber and/or QuickScrubber Plus pads and handles are included in each carton. Quantities vary depending on the QuickSeam product.

### Physical Properties:

Property	Value
QuickSeam Tape:	
Base	Rubber Polymers
Color	Black
Solvents	None
Solids	100%
Cured State	Cured
Thickness	0.020" (0.508 mm) ± 0.005" (0.127 mm)
Dimensions	18" X 18" (457.2 mm X 457.2 mm) with 3 ¼" diameter enter hole

# TECHNICAL INFORMATION SHEET

---

<b>Physical Properties:</b>	<i>Value</i>
<i>Membrane:</i>	
<i>Base</i>	EPDM, Non-reinforced
<i>Color</i>	Black
<i>Solvents</i>	None
<i>Cured State</i>	Cured
<i>Thickness</i>	0.060" (1.52 mm) ± 0.005"(0.127 mm)
<i>Width</i>	18" X 18"(457.2 mm X 457.2 mm) with 3 ¼" diameter center hole
<i>Release Liner:</i>	The tape portion of QS SA Patch for Conduit Flashing is protected by polymeric release liner, perforated to allow removal in separate sections to facilitate application.

Please Contact your Firestone Roof Systems Advisor at 1-800-428-4511 for further information.

*This sheet is meant to highlight Firestone products and specifications and is subject to change without notice. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. Neither Firestone nor its representatives practice architecture. Firestone offers no opinion on and expressly disclaims any responsibility for the soundness of any structure. Firestone accepts no liability for structural failure or resultant damages. Consult a competent structural engineer prior to installation if the structural soundness or structural ability to properly support a planned installation is in question. No Firestone representative is authorized to vary this disclaimer.*